

PRODUCT SAFETY DATA SHEET

PRODUCT: BASECOAT FOR FLAT EMULSION REVISION
NO: - 001
DATE OF ISSUE: JULY 2002 PAGE 1 of 3

1. IDENTIFICATION.
NAME: BASECOAT FOR FLAT EMULSION
USE: FOR APPLICATION BY BRUSH , ROLLER AND SPRAY.
MANUFACTURED BY: Paint Library
5 Elystan Street, London, SW3 3NT
Tel: 020 7590 9860 / Fax: 020 7823 7766

2. COMPOSITION/ INFORMATION ON INGREDIENTS.
The product does not contain any substance presenting a health hazard within the meaning of the CHIP Regulations.

3. HAZARDS IDENTIFICATION
The product is not classified as dangerous according to the CHIP Regulations (refer also to Section 11)

4. FIRST AID MEASURES.
General
In all cases of doubt, or when symptoms persist, seek medical attention.
Never give anything by mouth to an unconscious person.
Inhalation
Remove to fresh air, keep the patient warm and at rest. If breathing has stopped, administer artificial respiration. Give nothing by mouth. If unconscious, place in the recovery position and seek medical advice.
Eye Contact
Contact lenses should be removed. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart, and seek medical advice.
Skin Contact
Remove contaminated clothing. Wash skin thoroughly with soap and water or use a proprietary skin cleaner. Do NOT use solvents or thinners.
Ingestion
If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

5. FIRE FIGHTING MEASURES.
EXTINGUISHING MEDIA
Recommended: Alcohol resistant foam, Carbon Dioxide, Powder, Water spray/ mist.
Not to be used: Water jet.

RECOMMENDATIONS
Fire will produce dense black smoke containing hazardous products of combustion (See Section 10). Decomposition products may be a hazard to health. Appropriate self-contained breathing apparatus may be required. Cool closed containers exposed to fire with water spray. Do not allow run-off from fire fighting to enter drains or water courses.

6. ACCIDENTAL RELEASE MEASURES.
Avoid breathing vapours. Refer to protective measures listed in Sections 7 and 8. Contain and collect spillages with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container for disposal in accordance with the waste regulations (See Section 13). Do not allow to enter drains or water courses. Clean preferably with a detergent; avoid the use of solvents. If the product enters drains or sewers, the local water company should be contacted immediately; in the case of contamination of streams, rivers or lakes, the National Rivers Authority.

7. HANDLING AND STORAGE.
HANDLING
Keep the container tightly closed. Exclude sources of heat, sparks and open flame.
Avoid skin and eye contact. Avoid inhalation of vapour and spray mist.
Smoking, eating and drinking should be prohibited in areas of storage and use.
For Personal Protection, see Section 8.
never use pressure to empty: the container is not a pressure vessel.
Always keep in containers made of the same material as the supply container.
The Manual Handling Regulations may apply to the handling of containers of this product.

8. EXPOSURE CONTROLS/ PERSONAL PROTECTION.
ENGINEERING MEASURES.
Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and general good extraction. If these are not sufficient to maintain concentrations of particulates and/or solvent vapours below the relevant occupational exposure limits, suitable respiratory protective equipment should be worn (See Protective Protection below).

EXPOSURE LIMITS

SUBSTANCE	OCCUPATIONAL EXPOSURE LIMITS		NOTATIONS
	8 Hr TWA (1)	mg/m ³	
Respirable Particulates		5	OEL
Total Inhalable Particulates		10	OEL

NOTES
(1) Long term exposure limit - 8 hour time weighted average
(2) Short term exposure limit - 15 minute reference period
(3) "Sk" indicates a risk of absorption through the skin.
"Sen" indicates a respiratory sensitiser.

PRODUCT SAFETY DATA SHEET

PRODUCT:

BASECOAT FOR FLAT EMULSION

REVISION

NO: - 001

DATE OF ISSUE

JULY 2002

PAGE 2 of 3

8. Continued...

- (4) "OEL" indicates an Occupational Exposure Level
"MEL" indicates a Maximum Exposure Limit.
OELs are taken from the current version of EH40, except those marked "SUP", which are assigned by the supplier of the substance.

PERSONAL PROTECTION

All PPE, including RPE, used to control exposure to hazardous substances must be selected to meet the requirements of the COSHH Regulations.

RESPIRATORY PROTECTION.

Air-fed respiratory protective equipment should be worn when this product is sprayed if the exposure of the sprayer or other people nearby cannot be controlled to below the occupational exposure limit and engineering controls and methods cannot reasonably be improved.

HAND PROTECTION

When skin exposure may occur, advice should be sought from glove suppliers on appropriate types. Barrier creams may help to protect exposed areas of skin but are not substitutes for full physical protection. They should not be applied once exposure has occurred.

EYE PROTECTION

Eye protection designed to protect against liquid splashes should be worn.

SKIN PROTECTION

Cotton or cotton/ synthetic coveralls are normally suitable. Grossly contaminated clothing should be removed and the skin washed with soap and water or a proprietary skin cleaner.

9. PHYSICAL AND CHEMICAL PROPERTIES.

Physical State:	Viscous Liquid	
Viscosity:	8 – 12	Method: Rotothinner
Specific Gravity:	1.30 - 1.35	Method: Weight Cup
Vapour Density	Heavier	than Air.
Solubility in water:	Partially Miscible	

10. STABILITY AND REACTIVITY

Stable under the recommended storage and handling conditions (See Section 7).

In a fire, hazardous decomposition products such as smoke, carbon monoxide, carbon dioxide and oxides of nitrogen may be produced.

Keep away from oxidising agents and strongly alkaline and strongly acidic materials to prevent the possibility of exothermic reaction.

11. TOXICOLOGICAL INFORMATION

There is no data available on the product itself.

Repeated or prolonged contact with the product may lead to removal of natural fats from the skin resulting in non-allergic contact dermatitis and absorption through the skin. Splashes in the eyes may cause irritation and reversible local damage.

STORAGE

Observe the label precautions. Store between 5°C and 25°C in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Prevent unauthorised access. Containers which are opened should be properly re-sealed and kept upright to prevent leakage.

Store separately from oxidising agents and strongly alkaline and strongly acid materials.

12. ECOLOGICAL INFORMATION

There is no data available on the product itself.

The product should not be allowed to enter drains or water courses or be deposited where it can affect ground or surface waters.

The Air Pollution Control requirements of regulations made under the Environmental Protection Act may apply to the use of this product.

13. DISPOSAL CONSIDERATIONS

Do not allow into drains or water courses or dispose of where ground or surface waters may be affected.

Wastes, including emptied containers, are controlled wastes and should be disposed of in accordance with regulations made under the Control of Pollution Act and the Environmental Protection Act.

Using the information provided in this safety data sheet, advice should be obtained from the Waste Regulation Authority whether the Special Waste Regulations apply.

14. TRANSPORT INFORMATION

THIS PRODUCT IS NOT CLASSIFIED AS DANGEROUS FOR CARRIAGE

PRODUCT SAFETY DATA SHEET

PRODUCT:

BASECOAT FOR FLAT EMULSION

REVISION

NO: - 001

DATE OF ISSUE

JULY 2002

PAGE 3 of 3

15. REGULATORY INFORMATION

The product is determined as not being dangerous according to the CHIP Regulations.

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks as required by other health and safety legislation. The provisions of the Health and Safety at Work etc. Act and the Control of Substances Hazardous to Health Regulations apply to the use of this product at work.

16. OTHER INFORMATION.

This safety data sheet is provided in accordance with the provisions of Section 6 of the Health and Safety at Work, etc. act 1974, as amended by the Consumer Protection Act 1987.

The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.

The information contained in this safety data sheet is based on the present state of knowledge and current national legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

Further information and advice can be found in:

The Control of Substances Hazardous to Health Regulations 1988 (SI.1988:1657).

The Manual Handling Operations Regulations 1992 (SI 1992:2793)

The Environmental Protection (Duty of Care) Regulations 1992 (SI 1992:2839)
