

PAINT LIBRARY DP6

Household Emulsion (Flat Acrylic)

Description

A high opacity, pure acrylic resin based paint for use on interior or exterior surfaces. Dries to a matt finish with excellent covering power. Being virtually solvent-free it has a very low odour during application.

Surfaces

All common internal and external masonry surfaces including old plaster, plasterboard, cement render and suitably primed interior wood and metals surfaces subject to low traffic. Not suitable for radiators. May be used in kitchens and suitably ventilated bathrooms away from splash zones and areas of high condensation. Not recommended for use over PVA sealer, or in areas where a washable finish is required.

Pack Sizes	5 litres & 2.5 litres
Colour Range	Paint Library Architectural & Original
Spreading Rate	Up to 12 square metres per litre depending on surface profile and porosity. Typically 7-9 square meters per litre on pebbledash.
Drying Rate	Normally touch dry in 1-2 hours. Recoatable in 4 hours.

Technical Information

Sheen Level	Matt
Specific Gravity	1.20-1.38
Solids by Volume	34% approximately
Dry film Thickness	25-30 microns per coat on smooth surfaces 30-35 microns on external masonry surfaces

PAINT LIBRARY DP6

Household Emulsion (Flat Acrylic)

Preparation

Surfaces must be clean, dry and free from loose and flaking material, dirt, grease etc. Repairs should be carried out prior to painting. Areas contaminated with fungal or algal growth should be treated with a proprietary fungicidal wash or with 25% household bleach before painting. Powdery exterior surfaces should be brushed down and sealed with a masonry stabilising solution before painting. Surfaces previously treated with oil-based paint should be lightly abraded before painting.

Application

Stir well before use. Ready for use by brush, roller or airless spray. On porous surfaces up to 5% water may be added to assist application. On very porous surfaces e.g. plaster up to 25% water may be necessary. Two finishing coats will usually suffice on internal surfaces.

Clean up

Use clean water

Precautions

Always read the can label before use. Do not apply to surfaces below 5°C or if there is a risk of heavy rain or frost during application or drying.

September 2002